

firestar Matrix



Part #	Length	Height of Star - NG	Height of Star - LP	Gas Supply Line*	Fitting Size	Btu	WT
	Point to Point	w Fittings	w Fittings	(Minimum) "ID"			
DFS-9	9"	2 1/4"	3"	3/4"	3/8"	20,000	2
DFS-9P	9"	2 1/4"	3"	3/4"	3/8"	20,000	2
DFS-12	12"	2 1/4"	3"	3/4"	3/8"	36,000	3
DFS-12P	12"	2 1/4"	3"	3/4"	3/8"	36,000	3
DFS-18	18"	2 3/4"	3 1/2"	3/4"	1/2"	60,000	6
DFS-18P	18"	2 3/4"	3 1/2"	3/4"	1/2"	60,000	6
DFS-24	24"	2 3/4"	3 1/2"	1 1/4"	1/2"	100,000	8
DFS-24P	24"	2 3/4"	3 1/2"	1 1/4"	1/2"	100,000	8
DFS-30	30"	3 1/4"	4"	1 1/4"	1/2"	160,000	10
DFS-30P	30"	3 1/4"	4"	1 1/4"	1/2"	160,000	10
DFS-36	36"	3 1/4"	4"	1 1/4"	1/2"	200,000	19
DFS-36P	36"	3 1/4"	4"	1 1/4"	1/2"	200,000	19
<i>DFS-48</i>	48"	3 1/4"	4"	1 1/4"	1/2"	240,000	38
<i>DFS-48P</i>	48"	3 1/4"	4"	1 1/4"	1/2"	240,000	38

Items in italics are over sized for ground shipping, oversize shipping charges will apply

When planning the gas line for the fire feature on your project, use the table above to determine the amount of gas needed at the fire feature

*The Btu listed is estimated to produce 8" to 18" flames at up to a 70' gas run. For longer gas runs, consult your certified gas installer.

firestar facts:

firepit rings will fill with water when installed with ports up. Many install with ports down, which tends to lessen the flame height. The unique design of the firestar eliminates excessive water accumulation.

Warranty:

5 year Limited Warranty to the original purchaser in the original install application and location. Warranty in commercial application is one year from date of install to original purchaser in the original install application and location.